

## SPECIFICATIONS

|                      |                                                                                 |
|----------------------|---------------------------------------------------------------------------------|
| <b>System</b>        |                                                                                 |
| CPU                  | RK3588 -2.2Ghz                                                                  |
| GPU                  | ARM Mali400MP2, Complies with OpenGL ES2.0/1.1                                  |
| RAM                  | 8GB RAM                                                                         |
| ROM                  | 64GB NAND FAST FLASH                                                            |
| OS                   | Android 13                                                                      |
| <b>Display</b>       | 21.5 INCH                                                                       |
| LCD                  | BOE IPS Screen 1920x1080                                                        |
| Touchscreen          | 10 Point Capacitive Touch                                                       |
| Resolution           | (1920 x1080 pixel resolution)                                                   |
| LCD Panel Brightness | 400-500 cd/m2                                                                   |
| Wireless             | WIFI ( 802.11 b/g/n) dual band , Bluetooth 4.0                                  |
| Interface            | Audio, DC 12Vin, XLR, USB2.0x3, RJ45x1, Micro OTGx1, optional support for RS232 |
| Power Supply         | 12V/3A dc-in(100/240V) or PoE / 48V                                             |
| Speaker              | 1W (optional)                                                                   |
| Microphone           | Optional                                                                        |
| Camera               | 5MP (optional)                                                                  |
| Battery              | N/A                                                                             |
| Temperature          | Operating: -10°C to 60°C<br>Storage: -30°C to 80°C                              |
| Humidity             | Operating 20% to 80%                                                            |
| Weight               | 6.13 kg                                                                         |
| Certifications       | FCC, CE ROHS                                                                    |
| Mechanical           | VESA Mount from Rear, Metal Bracket                                             |
| Rugged Rating        | None                                                                            |
| Mounting             | on wall mount                                                                   |