

## Model:

## KA-DM412



## **Features**

- SONY IMX415 black light CMOS chip; Hisilicon high performance DSP;
- 20 x high resolution optical lens;
- 6 high-power infrared lamps,6pcs 3watt LED, night vision distance of 100 meters;
- Built-in 5 w power horn/microphone, two-way intercom. Custom voice prompts;
- Al multi-point human tracking.

## **Package Details**

- 1. 1\* POE IP Camera;
- 2. 1\* Pack of Screws and Screwdriver;
- 3. 1\*English User Manual.

	POE	Camera_Speed Dome (support onvif)
Model		KA-DM412 8MP
Camera	sensor	1/2.8" CMOS SSC338Q+IMX415
	resolution ratio	8MP
	signal pattern	NTSC/PAL
	Effective pixel	3840 (H) x2160 (V)
	Minimum	Color:0.01Lux,B/W:0.001Lux
	S/N radio	>60dB
	White balance	Auto
	Electronic shutter	PAL:1/25 ~ 1/100000s NTSC:1/30 ~ 1/100000s
	Focus length	4.7~94mm
	Optical focus	20X
	Focus system	Auto/Manual
	Two-way voice	5W Horn, microphone
	Presets	100
	IR distance	100M
	POE	Support
	LED light control	Intelligent control technology
	LED light angle	Automatic adjustment
	Horizontal range	360°Continuous rotation
	Vertical range	-90°-0°
	Preset call speed	Max 80°/S
	Manual call speed	0.01°~80°/S
General	Working power supply	DC12V/4A
	waterproof	IP66 (Both indoor and outdoor)
	Gross weight	2KG
	Material	Metal + Plastic Housing,Indoor and outdoor Use
	Installation	Walls(optional suspension)
	Weight(kg)	1.8KG/PC
	Box size/weight	1PC/CTN: 18*18*30cm; 2kgs
	Carton size/weight	4PCS/CTN: 38.5*38.5*30.5cm; 9kgs