

Model:
KA-BT01-POE

Main Features

- full color and Infrared (IR) Night vision two mode;
- H.265X/ H.264 compression ;
- Built-in Microphone for Audio Surveillance;
- Built-in speaker for 2 way talk;
- Waterproof level IP66;
- Support Standard ONVIF comatible with most NVR and XMEYE series NVR ;
- Support P2P Remote Access/Multi-User View & anywhere & anytime;
- Elegant outline and easy installation;
- Provide Android & iOS XMEYE APP and professional CMS PC client software.

Package Details

1. 1* POE IP Camera;
2. 1* Pack of Screws and Screwdriver;
3. 1*English User Manual.

POE Audio Camera(support onvif)

| Model | KA-BT01-POE 4MP | KA-BT01-POE 5MP | KA-BT01-POE 8MP | |
|--------------------|---|---|--|--|
| Camera | Image Sensor | GK7205V210+SC5239S | GK7605V100+SC5339 | NT98566+SC8239 |
| | Megapixel | 4MP(2560*1440) | 5MP(2592*1944) | 8MP(3840*2160) |
| | Lens | 4mm default (6/8mm optional) | | |
| | Min.illumination | 0.1LUX/F1.2 | | |
| | Day&Night mode | IR CUT | | |
| | Night Vision distance | 0-20m Night Vision | | |
| Video | Video compression standard | H.265 +(Compatible with H.265/H.264) | | |
| | Video streaming | Dual streaming | | |
| | Video resolution | JPEG stream :(Monitoring for mobile phones) | | |
| | Video frame rate | Main stream:2560*1440@18fps, 2304*1296@20fps,1920*1080@25fps; sub-stream: 800*448@25fps | Main stream:2880*1616@20fps 2560*1440@25fps 2304*1296@25fps 1920*1080@25fps; sub-stream: 800*448@25fps | Main stream:8M 3840*2160@15fps, 5MP 2880*1616@25fps, 4MP2560*1440@25fps, 2MP1920*1080@25fps; sub-stream: 800*448@25fps |
| | Image settings | Brightness,saturation,contrast,Sharpness,Exposure,flip,mirror | | |
| Image enhancement | Backlight compensation,Automatic white balance Digital WDR, 3D digital noise reduction | | | |
| Audio | Audio compression | G.711A | | |
| | Audio Input | Support, Built-in Microphone 10M | | |
| | Audio Output | Support,can connect external Speaker | | |
| Function | Motion detecting | Support 1 independent screen detection | | |
| | Alarm linkage | To mailbox,FTP server,Micro SD card,message push | | |
| | Storage | Storage by NVR | | |
| | User management | Supports user and rights management | | |
| Interface | Network protocol | TCP/IP,HTTP,TCP,ICMP,UDP,ARP,IGMP,SMTP,FTP DHCP,DNS,DDNS,NTP,UPNP,RTSP etc. | | |
| | Connection protocol | Support ONVIF 2.4(backward compatible) | | |
| | Power interface | 1*5.5mm power interface | | |
| Power | Ethernet | 1*RJ45 & Antenna 10M/100M Adaptive Ethernet Interface | | |
| | Reset button | Support | | |
| Power | Power supply | POE / DC 12V/2A | | |
| | Power consumption | ≤3W | | |
| General | Working environment | Temperature: '-10— +50℃ , Humidity:10%—90% | | |
| | Material | Metal Housing,Indoor and outdoor Use | | |
| | Installation | Wall | | |
| | Size(W×D×H)(cm) | 7*7*20cm | | |
| | Weight(kg) | 0.27KG/PC | | |
| | Box size/weight | 1PC/CTN: 20*11*10cm; 0.37kgs | | |
| Carton size/weight | 30PCS/CTN: 53*32*40cm; 13.2kgs | | | |