

## Model:

**KA-7504POE**



## Features

- Support multi-languages ;
- Supports human shape detection and face detection(XMEye smart front-end equipment);
- H.265 High profile compression.Faster loading speed,more smooth video ;
- Advanced Motion Detection Recording and E-mail Alerts ;
- VGA/HD-OUT High definition display,HD-OUT/VGA/TV output simultaneously ;
- Support IE, Chrome, Firefox and Safari browsers;
- Support smart phone and pad remote monitor ;
- Remote Access Anytime, Anywhere,APP"XMeye Pro" & PC Software"VMS".

## Package Details

1. 1\*4CH POE NVR;
2. 1\*NVR Power Adapter;
3. 1\*Mouse;
4. 1\*Pack of Screws
5. 1\*English User Manual.

## POE NVR ( with Audio out )

Model		KA-7504POE
System	Operating system	Embedded LINUX
	System resource	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operation interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	0.25
Video	Video input(IP)	4*4K ( Access bandwidth 72Mbps )
	Video standard	PAL; NTSC
	Video compression	H.265A/H.265+(compatible H.265/H.264)
	Display quality	Max 4K
	Playback quality	4K/5M/4M/3M/1080P
	VR	Unsupport
Audio	Human shape / Face	Support (Depend on camera)
	Audio compression	G.711A
Record & Playback	Intercom	Support
	Recording mode	Manual>alarm>motion detection>timing
	Local payback	4K ( 1 ) /5M ( 1+1 ) /4M(2+1) /3M ( 3+1 ) /1080P ( 5+1 )
	Search mode	Search by Time/Calendar/Event/Channel
	Record storage	HDD、 Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch VGA,1ch HDMI HD output
	Audio I/O	1/1 ( 3.5MM)
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port
	USB interface	2*USB2.0 ports
	HDD	1 SATA ports,max support 12TB (HDD is option)
	ESATA	No
	Serial interface	No
General	PC/Laptop Remote	Support web, CMS, center platform management software XMEYE
	ONVIF	Support ONVIF, access third party
	Power	DC52V 2.3A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:-10℃ - + 55℃ , Humidity:10%- 90%RH , Atm:86kpa- 106kp
	Size(W×D×H)(mm)	26* 21.5*4.3cm
	Weight(kg)	0.82kgs
	Box size/weight	1PC/BOX: 34.5*7.5*28cm; 2.8kgs
Carton size/weight	20PCS/CTN: 65*43*63cm; 27.8kgs	